

















INTRODUCTION

Patented c series LED sports lights have an elegant appearance with die-cast modules, IK rating is IK08

Vertically and horizontally rotatable heat sink design makes every module flexibly targeting to specified point to get much better light uniformity on sports field.

Upward light ratio=0 for light fixture with symmetrical beams and spill covers Upward light ratio=0 for light fixture with asymmetrical beams

Optional long distance wireless control system and DMX control system



SPECIFICATIONS

Input Voltage	AC90-305V/AC108-528V		Housing	Housing		Aluminum			
LED Brand	Lumileds 5050		Rotatable Modular Design		gn Horizonta	Horizontally15°			
CRI	70 80 90		Wattage/Module			Symmetrical: 180W Asymmetrical: 150W			
Operating Temp	-40°C To 55°C		Dimming Solutions		0-10V Dim	0-10V Dimming, DALI, DMX, clo, Zigbee			
Power Factor	>0.95		ССТ		3000K 40	3000K 4000K 5000K 5700K 6500K			
Warranty	5 Yrs Warranty		Wireless Control		Available	Available			
IP Rate	IP66		Beam Angle		20°, 40°, 6	20°, 40°, 60°, asymmetric A60, A60W, A70, A70W			
Bracket	Stainless steel		Driver		INVENTRO	INVENTRONICS, MEANWELL, SOSEN			
IK Rate	IK08		Windload Test		17 class w	17 class windload(56.1-61.2m/s, 240kg/square meter)			
L70 Hour	>100.000h		Optional Accessories		SPD, Zigb	SPD, Zigbee Gateway, Zigbee Controller, Zigbee Wall Switch			
MODEL	SG-JR-180W	SG-JR-360W	SG-JR-540W	SG-JR-720W	SG-JR-900W	SG-JR-1080W	SG-JR-1440W	SG-JR-1800W	
WATTAGE Symmetrical	180W	360W	540W	720W	900W	1080W	1440W	1800W	
MODEL QTY	1	2	3	4	5	6	8	10	
LUMEN EFFICIENCY Symmetric	170LM/W	170LM/W	170LM/W	170LM/W	170LM/W	170LM/W	170LM/W	170LM/W	
LUMEN OUTPUT	30600LM	61200LM	91800LM	122400LM	153000LM	183600LM	244800LM	306000LM	
MODEL	SG-JR-150W	SG-JR-300W	SG-JR-450W	SG-JR-600W	SG-JR-750W	SG-JR-900W	SG-JR-1200W	SG-JR-1500W	
WATTAGE Asymmetrical	150W	300W	450W	600W	750W	900W	1200W	1500W	
MODEL QTY	1	2	3	4	5	6	8	10	
LUMEN EFFICIENCY Asymmetrical	145LM/W	145LM/W	145LM/W	145LM/W	145LM/W	145LM/W	145LM/W	145LM/W	
LUMEN OUTPUT	21750LM	43500LM	65250LM	87000LM	108750LM	130500LM	174000LM	217500LM	

remark: lumen output varies by the beam angles, CCT, CRI, etc, please contact us to get more specific data if needed

iBeam Sportsfield Lighting Member of Novilum BV Page 2



Obtrusive Light Control Solution

The application of asymmetric lenses help cut off all the obtrusive light from the back and upward.



DMX Control Entertainment System

••••••

 ${\sf SOGA}$ DMX entertainment system is designed to provide different flashing effects to players and fans.

Rotatable Modular Design

Each module can be rotated Horizontally 15°, bringing more flexible lighting solutions and more precise light targeting.



Long Distance Wireless Control System

No Wires Exposed To Avoid Bird Pecking



Stainless Steel Conduit

Protect the cable from any potential damage, like bird, rugged weather etc.

Protection Mesh Cover on Back

Keep the lamp always clean from the bird droppings or leaves, avoid the birds build the nests on lamp. The perfect heat dissipation performance $\frac{1}{2} \int_{-\infty}^{\infty} \frac{1}{2} \left(\frac{1}{2} \int_$

iBeam Sportsfield Lighting Member of Novilum BV Page 3



OBTRUSIVE LIGHT CONTROL SYSTEM





JAGUAR Series LED sports light delivers precise asymmetric light distributions, unique backlight cut-off control avoid spill light in the neighborhood, that makes EAGLE Series LED sports lights the best choice for high residential area and professional sports stadium.

Installation angle less than 10°

Comply with following glare control standards:

- ✓ EN 12193: 2018 Standard







OPTIONAL ACCESSORIES




20KV SPD

Zigbee Gateway

Zigbee Controller

PRODUCT SIZE





iBeam Sportsfield Lighting Member of Novilum BV Page 5


SG-JR-450W



PRODUCT SIZE







APPLICATION









TENNIS COURT

HIGH POLE LIGHT

OUTDOOR PARKING

FOOTBALL FIELD